




DESIGN

<p>Tufted Pile Weight: 16.0 oz. per sq. yd. (542 g/m²)</p> <p>Product Type: Tile</p> <p>Construction: Tufted</p> <p>Minimum Sq. Yd.: No Minimum</p> <p>Surface Texture: Level Patterned Loop</p> <p>Gauge: 1/10 (39.37 rows per 10 cm)</p> <p>Density: 5,189</p> <p>Weight Density: 83,027</p> <p>Stitches Per Inch: 10.4 (40.94 per 10 cm)</p> <p>Finished Pile Thickness: .111" (2.82 mm)</p> <p>Dye Method: Solution Dyed</p> <p>Backing Material: EcoFlex Matrix</p> <p>Fiber Type: Colorstrand® SD Nylon</p> <p>Pattern Repeat: Not Applicable</p> <p>Size: 24" x 24" (.6096 m x .6096 m)</p> <p>Installation Method: Quarter Turn, Monolithic, Brick Ashlar, Vertical Ashlar, Multi Directional</p> <p>Stain Release Technology: Sentry Plus Stain Protection</p> <p>Soil Release Technology: Sentry Soil Protection</p> <p>Foot Traffic Recommendation TARR: Heavy</p>
--



989
Carbon
Quickship Available

SUSTAINABILITY

<p>IAQ Green Label Plus: CRI Green Label Plus GLP1171</p> <p>Pre-Consumer Recycled Content: 53%</p> <p>NSF 140: EcoFlex Matrix - NSF 140 Gold</p> <p>Declare Label: Declared Red List Free</p>
--

PERFORMANCE

<p>Static: AATCC-134 Under 3.5 KV</p> <p>Flammability: ASTM E 648 Class I (Glue Down)</p> <p>Smoke Density: ASTM E 662 Less than 450</p>
--

SERVICE

<p>Warranties: Lifetime Limited Carpet Tile Warranty, Lifetime Limited Colorfastness to Light, 10 Year Colorfastness to Atmospheric Contaminants, 10 Year Stain Warranty, 10 Year Limited Static</p>
--