



**DESIGN**

|                           |                                    |
|---------------------------|------------------------------------|
| Tufted Pile Weight:       | <b>18 oz/yd2 (610 g/m2)</b>        |
| Product Type:             | <b>Broadloom</b>                   |
| Construction:             | <b>Tufted</b>                      |
| Minimum Sq. Yd.:          | <b>No Minimum</b>                  |
| Surface Texture:          | <b>Textured Patterned Loop</b>     |
| Gauge:                    | <b>1/10 (39.37 rows per 10 cm)</b> |
| Density:                  | <b>4,468</b>                       |
| Weight Density:           | <b>80,441</b>                      |
| Stitches Per Inch:        | <b>12.6 (49.61 per 10 cm)</b>      |
| Finished Pile Thickness:  | <b>.145" (3.68 mm)</b>             |
| Dye Method:               | <b>Solution Dyed</b>               |
| Backing Material:         | <b>Weldlok®</b>                    |
| Fiber Type:               | <b>Envirostrand® SD PET</b>        |
| Pattern Repeat:           | <b>0.6" (W) x 0.8" (L)</b>         |
| Width:                    | <b>12' width (3.66 m)</b>          |
| Stain Release Technology: | <b>Sentry Soil Protection</b>      |
| Soil Release Technology:  | <b>Sentry Soil Protection</b>      |

**SUSTAINABILITY**

|                                 |                                     |
|---------------------------------|-------------------------------------|
| IAQ Green Label Plus:           | <b>CRI Green Label Plus GLP0350</b> |
| Post-Consumer Recycled Content: | <b>35%</b>                          |

**PERFORMANCE**

|                |                                       |
|----------------|---------------------------------------|
| Static:        | <b>AATCC-134 Under 3.5 KV</b>         |
| Flammability:  | <b>ASTM E 648 Class 1 (Glue Down)</b> |
| Smoke Density: | <b>ASTM E 662 Less than 450</b>       |

**SERVICE**


|             |  |
|-------------|--|
| Warranties: | <b>10 Year Limited Wear Warranty, 10 Year Limited Static Protection Warranty, 10 Year Stain Resistance Warranty, 10 Year Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants</b> |
|-------------|--|



**383**  
Perfect Results  
Quickship Available




**599**  
Take Action  
Quickship Available




**788**  
Radiate Wisdom  
Quickship Available



**889**  
Progressive Way  
Quickship Available



**949**  
Quiet Factor  
Quickship Available



**997**  
Starting New  
Quickship Available



**999**  
Special Task  
Quickship Available